TECHNICAL DATA SHEET

EASY MIX BRICKIES LOAM



March 2020

PRODUCT DESCRIPTION

Easy Mix Brickies Loam is a specially graded and proportioned sand/loam blend which when combined with portland cement and water creates a workable, plastic mortar suitable for the installation of clay or concrete masonry.

The product is packaged ready for use at a natural moisture content which mimics site prepared materials.

PRODUCT ADVANTAGES

- Specially graded sand for consistency and size
- Easy trowelling formula
- Reduced dustiness
- All weather packaging

PRODUCT PACKAGING

Easy Mix Brickies Loam is available in 20kg plastic bags.

TECHNICAL DATA

Easy Mix Brickies Loam can be combined with various cements and hydrated lime to produce a workable, plastic mortar.

Proportioning guidelines for mortars suitable to lay clay bricks and concrete blocks are shown below.

PARTS BY VOLUME

Mortar	Cement	EM Brickies Loam	Lime
M3	1	6	1
M4	1	4.5	0.5

Add water to the chosen mixture and mix to produce the desired mortar consistency according to conditions and application.

For additional consistency, air entraining admixtures can also be used with the mix water. Follow manufacturer guidelines in relation to dosages to be used.

PRODUCT STORAGE

Product can be stored externally if required. Undercover storage will extend packaging life from UV deterioration.

USAGE PRECAUTIONS

Aggregate such as sand maybe irritating to the eyes, skin and lungs. Always avoid contact with the eyes and skin and take precautions to avoid breathing dust.

For further information consult the Safety Data Sheet (SDS) and always read the product label carefully before use.

Safety Data Sheets are available on www.easymixsales.com.au

Please Note:- The information given in this data sheet is based on our current knowledge of the product when properly stored, handled and applied. We cannot guarantee that the product will be suitable, effective or safe when used for any purpose other than its stated uses. To the extent that it is lawful, we exclude warranties implied by law and limit our liability to the cost of replacing the product. We accept no responsibility for loss or injury caused by improper use, incompetent preparation, inexpert or negligent application, or ordinary wear and tear. Service or advice given by our staff should not amount to responsibility for the project - since the owner, or their contractor (and not River Sands), is responsible for procedures relating to the application of the product

